

Signet 8750 pH/ORP Transmitters



Check out the 9900 Transmitter for your single channel needs

Member of the ProcessPro® Family of Instruments



Panel Mount



Pipe, Tank, Wall Mount

The Signet 8750 pH/ORP Transmitter is designed for broad application and ease of setup and use. The unit auto-configures for either pH or ORP use when connected to Signet pH or ORP electrodes. Multiple mounting options allow for installation best suited to your particular application.

The EasyCal menu features automatic buffer recognition for mistake-proof pH or ORP electrode calibrations. Intuitive software and the four button keypad arrangement make it easy to access important information such as pH or ORP, mV input, temperature, calibration, relay setup menus and more.

Features

- Automatic temperature compensation
- Temperature display in °C or °F
- Hold and simulate functions
- Relay options available
- Output scalability
- Dual output
- NEMA 4X/IP65 enclosure with self-healing window
- EasyCal



Applications



- Neutralization Systems
- Heavy Metals Recovery
- Plating Control
- Scrubber Control
- Pool and Spa Control
- Environmental Study
- Water Treatment
- Water Quality Monitoring
- Waste Treatment
- Disinfection

Specifications


General			
Accuracy	±0.03 pH, ±2 mV ORP		
Display	2 x 16 LCD		
	Contrast	User selectable, 5 levels	
Material			
Case	PBT		
Panel Case Gasket	Neoprene		
Window	Polyurethane coated polycarbonate		
Keypad	Sealed 4-key silicone rubber		
Electrical			
Power	12 to 24 VDC ±10% regulated		
	60 mA max.		
Electrode Input Range	pH	0 to 14 pH	
	Temp.	3K Balco, -25 °C to 120 °C	-13 °F to 248 °F
	ORP	-1000 to +2000 mV, isolated	10 KΩ I.D. resistance T+, T-
Current Output	4 to 20 mA, isolated, passive, fully adjustable and reversible		
	Max. Loop Impedance	50 Ω max. @ 12 V	325 Ω max. @ 18 V 600 Ω max. @ 24 V
	Update Rate	0.5 seconds	
	Accuracy	±0.03 mA @ 25 °C, 24 V	
Relay Output	Mechanical SPDT contacts	High, Low, Pulse, Off	
	Maximum Voltage Rating	5 A @ 30 VDC, or 5 A @ 250 VAC resistive load	
	Hysteresis	User-adjustable Max 400 pulses/min.	
	Open-Collector Output	High, Low, Pulse, Off	
		Optically isolated, 50 mA max, sink, 30 VDC max. pull-up voltage.	
	Hysteresis	User-adjustable Max. 400 pulses/min.	
Environmental			
Operating Temperature	-10 °C to 70 °C	14 °F to 158 °F	
Storage Temperature	-15 °C to 80 °C	5 °F to 176 °F	
Relative Humidity	0 to 95%, non-condensing		
Enclosure	NEMA 4X/IP65 (front face only on panel mount); field mount is 100% NEMA 4X/IP65		
Shipping Weight			
	0.6 kg	1.3 lb	
Standards and Approvals			
	CE, FCC, UL, CUL		
	RoHS compliant, China RoHS		
	Manufactured under ISO 9001 for Quality and ISO 14001 for Environmental Management and OHSAS 18001 for Occupational Health and Safety		

Dimensions

3-8750-XP Panel Mount


















Field version with Universal Mounting Kit



In-line Installation

Wet-Tap Installation


Submersible Installation

System Overview	Panel Mount Signet Instrument 8750 	Pipe, Tank, Wall Mount Signet pH/ORP Transmitter 8750 with Signet Universal Mount Kit (3-8050) 	Panel Mount Signet Instrument 8750 	Pipe, Tank, Wall Mount Signet pH/ORP Transmitter 8750 with Signet Universal Mount Kit (3-8050) 	Panel Mount Signet Instrument 8750  
	Signet Pre-amplifier 2760 	Signet 2760 Pre-amplifier with Signet Wet-Tap Electrode 2756 2757 	Signet 2760 Pre-amplifier with customer supplied pipe extension or conduit, 3/4 in. NPT or ISO 7/1-R 3/4 threads** 		
	Signet Electrodes 2724-2726 2764-2767 2774-2777 	Signet 3719 Wet-Tap 	Signet Electrodes 2724-2726 2764-2767 2774-2777 		
	GF Fittings* or customer supplied fittings 	GF Tees and Fittings see model 3719 for more info 	All sold separately 		

*See fittings section for more information.

**Refer to the Signet Submersion brochure located in the K-Factors Fittings and More Kit (3-0000-709) for installation suggestions and options.

Ordering Information



Mfr. Part No.	Code	Input	Output	Power
Field Mount pH/ORP Transmitter yellow body for pipe, wall, or tank mounting				
3-8750-3	159 000 057	One	two 4 to 20 mA outputs and 2 open collectors	4 wire
Panel Mount pH/ORP Transmitter black body; including mounting bracket and panel gasket				
3-8750-3P	159 000 058	One	two 4 to 20 mA outputs and 2 open collectors	4 wire

Please refer to **Wiring, Installation, and Accessories** sections for more information.

Model 8750 Ordering Information

- 1) For panel version, cutout should be 92 x 92 mm (3.62 x 3.62 in.)
- 2) To mount the panel version on a wall, use the heavy duty wall mount bracket.
- 3) An optional splashproof rear cover can be ordered separately if needed - panel mount version only.
- 4) Use the universal mounting kit with the field mount instrument to mount to a pipe, tank or wall.
- 5) Order RC filter kits to protect relays from voltage spikes.

Accessories and Replacement Parts

Mfr. Part No.	Code	Description
Mounting		
3-8050	159 000 184	Universal mounting kit
3-8050.392	159 000 640	¼ DIN retrofit adapter
3-8050.395	159 000 186	Splashproof rear cover (panel mount only)
3-0000.596	159 000 641	Heavy duty wall mount bracket (panel mount only)
3-5000.598	198 840 225	Surface mount bracket (panel mount only)
3-9900.396	159 001 701	Angle adjustment adapter kit
Liquid Tight Connectors		
3-9000.392	159 000 368	Liquid tight connector kit for rear cover (3 connectors)
3-9000.392-1	159 000 839	Liquid tight connector kit, NPT (1 connector)
3-9000.392-2	159 000 841	Liquid tight connector kit, PG 13.5 (1 connector)
Other		
3-8050.396	159 000 617	RC filter kit (for relay use), 2 per kit
3-0700.390	198 864 403	pH buffer kit (1 each 4, 7, 10 pH buffer in powder form, makes 50 ml of each)
3-8050.625-70	159 001 654	Clear window display with adhesive

3-8750.099 Rev E (4/13)

© Georg Fischer Signet LLC

3401 Aero Jet Avenue, El Monte, CA 91731-2882 U.S.A. • Tel. (626) 571-2770 • Fax (626) 573-2057 • www.gfsignet.com • e-mail: signet.ps@georgfischer.com
 Specifications subject to change without notice. All rights reserved. All corporate names and trademarks stated herein are the property of their respective companies.

www.gfsignet.com